



AMK PLASTICS, L.L.C.
7120 NW 51st Street, Miami FL 33166
Tel. 305-470-9088 Fax. 305-470-9091

Foot Sealer, KF-Series



YOUR ONE SOURCE OF PLASTIC MACHINERY & MATERIAL SUPPLIER



KF-Series foot sealers are ideal for high volume poly bag and other thermoplastic sealing. The sealers are capable of sealing 15-20 bags per minute. These sealers allow you to keep both hands free for quicker and more accurate sealing. The machines are also equipped with a plug-in timer. The timer controls the sealing time needed for different materials. Once the timer is set, it will give a consistently flat seal. When the seal is done, the signal light on the timer will turn off.

KF-Series foot sealers are available in 12", 18", and 24" lengths with a 2.5mm or 5mm wide seal. Our 2.5mm seal width units are ETL Listed. Depending on the the model of the sealer, materials up to 24" wide and 16 mil total thickness can be sealed. The sealers include a 26" pedestal, a 2" base, an adjustable work table with an adjustable foot control.

Easy to Operate: Set the timer. Insert the bag between the two sealing bars and press down on the foot board. Hold down the foot board for an additional 2-3 seconds after the timer light goes off to set the seal.

FEATURES:

- Ideal for high volume sealing
- Plug-in electronic time for variable control
- All metal construction
- No warm-up time
- Sits on rectangular base for stability
- ETL Listed (2mm seal width only)

Direct heat / constant heat sealers seal many types of thermoplastic packaging material, but are especially ideal for thicker material such as coated aluminum foil, Kraft paper, cellophane, mylar, coated PP. Please note: direct heat sealers cannot seal polyethylene. Depending on the model of the sealer, material up to 16" wide and 20 mil thick can be sealed. The meshed seal width is 10mm. Equipped with a digital temperature controller that accurately controls the temperature from 125°-600° F (50°-320°C). Both jaws are heated simultaneously resulting in better heat penetration to seal thicker material. Units also include an adjustable work table.



Specifications:

	Seal Length	Seal Width	Watts
KF-300F*	12"	2.5MM	400W
KF-305F	12"	5MM	600W
KF-450F*	18"	2.5MM	600W
KF-455F	18"	5MM	900W
KF-600F*	24"	2.5MM	800W
KF-605F	24"	5MM	1200W