

# SHRINK PACKAGING MACHINE MAQUINA DE EMPAQUE TERMOENCIGIBLE



Model SY-4646-FA



## AMK PLASTICS LLC

7120 N.W. 51 STREET, MIAMI, FLORIDA 33166

TEL: 305-470-9088 FAX: 305-470-9091


Web: [www.amk-plastics.com](http://www.amk-plastics.com) Email: [amk@amk-plastics.com](mailto:amk@amk-plastics.com)

Our Model SY-4646-FA Shrink Packaging Machine has the features of stacking, wrapping, shrinking and cooling—all in a continuous and fully automatic motion. Capturing the latest European technology, the Model SY-4646-FA is well equipped with world known brand name components. It is suitable and ideal for products such as beers, cans, bottle water, drinks and daily commodities to list a few. It works with PE as well as PVC, either with or without a tray.

We also have a semi-automatic version that has the similar features as the fully automatic except that the stacking is manually operated.

Nuestra maquina Termoencogible Modelo SY-4646-FA tiene las características de amontonar, envolver, encoger y enfriar—todas totalmente automáticas en un movimiento continuo, Capturando lo ultimo en tecnología Europea, el Modelo SY-4646-FA esta muy bien equipado con componentes de marcas bien conocidas mundialmente. Es apropiada e ideal para productos tales como, cerveza, latas, botellas para agua, refrescos y artículos del diario, solo para mencionarle algunos. Trabaja con PE al igual que con PVC, funcionando con o sin bandeja.

También tenemos una versión semi-automática con características similares a la totalmente automática excepto que el amontonador se opera manualmente.



Specifications	Especificaciones	
Horizontal height and Length of infeed conveyor	Alto horizontal y largo del Alimentador de tren de arrastre	850 ± 50mm/1500mm
Max. package dimension(mm)	Max. dimension de empaque(mm)	L600 × W300 × H300
Packing speed	Velocidad de empaque	0-12m/min
Power Consumption	Energia	3Φ/220V/380V 50/60HZ 2KW
Air source	Fuente de aire	0.6Mpa(6Kg/cm <sup>2</sup> )
Sealing time/temperature	Tiempo/temperatura de sellado	0.5-1.5S/0-250°C
Width of film/thickness	Ancho de la película/grueso	MAX650mm/0.04-0.12mm
Dimension (mm)	Dimension (mm)	L1500 × W2700 × H2000
Net weight	Peso neto	550kg

